



	Company	Offer-/Order-No.			
	<b>INSTRUMENT TYPE</b>	or			
<b>A</b>	<b>Piping</b>				
1	Line size	DN	PN		
2	Process connection	Threat	G		
		Flange	DIN	ANSI	DN PN
3	Flow direction	⇒	⇐	⇓	⇑
4	Max. Flow	m <sup>3</sup> /h			
5	Setpoint:	m <sup>3</sup> /h	or adjustable from		m <sup>3</sup> /h to m <sup>3</sup> /h
6	Calibrated to	Flow increasing	decreasing		
<b>B</b>	<b>Media</b>				
1	Specific gravity	kg/m <sup>3</sup>			
2	Operating pressure	bar			
3	Operating temperature	°C			
4	Viscosity	cSt	at	°C	
<b>C</b>	<b>Operation condition</b>				
1	Atmosphere				
2	Ambient temperature	-20°C ... +40°C or			
3	Ex-protection DIN EN 60529	No	EX(de)	EX(i )	
4	High temperature application	No	Yes		
5	Unit weather proof DIN 40050	IP 65	or		
<b>D</b>	<b>Material of wetted parts</b>				
1	Flange	1.4571	or		
2	System tube	1.4571	or		
3	Other wetted parts	1.4571	or		
4	Switching house ∅ 120 mm, h 70 mm	AL	SS	RB	
<b>E</b>	<b>Electrical parts</b>				
1	Switch	Magnetic contact:	1	2	SPDT
		Micro-switch:	1	2	SPDT
		Inductiv contact: nach NAMUR	1 n.c.		1 n.o.
	<b>Remarks</b>				